

Sani-Tech® STHT®-C Sanitary Silicone Tubing

Laser
Marked



Permanently laser marked with part number and lot code for total product traceability.

Sani-Tech® STHT®-C

Sani-Tech® STHT®-C is an ultra-pure, biopharmaceutical-grade tubing that has a useful life unmatched by any other known process tubing. Sani-Tech® STHT®-C platinum-cured silicone tubing resists temperature extremes, ozone, corona, radiation, moisture, compression sets, weathering and chemical attack and imparts no taste or odors to fluids transported within it. Sani-Tech® STHT®-C silicone tubing withstands repeated autoclaving and resists the adherence of blood products and other sanitary fluids. Sani-Tech® STHT®-C, in 1/16" ID and greater, comes with laser marked part numbers and lot codes to provide total product traceability.

Characteristics

The manufacturing process is carefully controlled from receiving through production. Inspection and lot traceability are readily accessible as batch numbers are assigned. All packages are identified by external labeling on both the bag and the high-quality, crush-proof box.

Biocompatibility

Sani-Tech® STHT®-C is manufactured from the finest grade of silicone materials and is fully characterized, validated and tested to a variety of specifications including USP Class VI criteria, ISO 10993, European Pharmacopoeia 3.1.9, and Japanese Pharmacopoeia – Section 51. For additional compliance data please contact our customer service department. Sani-Tech® STHT®-C has a Master File with the U.S. Food and Drug Administration.

BIOPHARMACEUTICAL PRODUCTS

Clear platinum-cured non-reinforced silicone tubing

Features/Benefits

- Ultra-pure, biopharmaceutical-grade silicone
- Permanently laser marked with part number and lot code for total product traceability
- Unsurpassed surface smoothness
- Ultra-flexible
- Autoclavable and sterilizable
- Temperature range from -80°F (-62°C) to 500°F (260°C)
- Imparts no taste or odors
- Available in bulk or assemblies
- Available in 25-, 50- and 100-foot coils

Typical Applications

- Sterile fill and transfers
- Drug delivery
- Media processing
- Sanitary peristaltic pump tubing
- Laboratory use
- Cell harvest
- Media processing
- Liquid chromatography

Sani-Tech® STHT®-C Tubing Available Sizes

Part Number	ID (inches)	OD (inches)	Wall (inches)	Pressure Rating		Part Number	ID (inches)	OD (inches)	Wall (inches)	Pressure Rating	
				Burst (psi)	Working (psi)					Burst (psi)	Working (psi)
STHT-C-012-0	0.012	0.024	0.006	48	10	STHT-C-250-3	0.25	0.438	0.093	41	8
STHT-C-020-0	0.02	0.036	0.008	41	8	STHT-C-250-4	0.25	0.5	0.125	52	10
STHT-C-025-0	0.025	0.047	0.011	44	9	STHT-C-250-5*	0.25	0.625	0.187	74	15
STHT-C-030-0	0.03	0.066	0.018	56	11	STHT-C-250-6*	0.25	0.75	0.25	105	21
STHT-C-030-2	0.03	0.155	0.062	161	32	STHT-C-312-1	0.312	0.375	0.032	17	3
STHT-C-040-0	0.04	0.086	0.023	54	11	STHT-C-312-2	0.312	0.438	0.062	22	4
STHT-C-058-0	0.058	0.076	0.009	24	5	STHT-C-312-3	0.312	0.5	0.093	41	8
STHT-C-062-1	0.062	0.125	0.032	51	10	STHT-C-312-4	0.312	0.563	0.125	48	10
STHT-C-062-2	0.062	0.188	0.062	85	17	STHT-C-312-5	0.312	0.688	0.187	69	14
STHT-C-062-3	0.062	0.25	0.093	118	24	STHT-C-312-6*	0.312	0.813	0.25	90	18
STHT-C-062-4	0.062	0.313	0.125	164	33	STHT-C-375-1*	0.375	0.438	0.032	14	3
STHT-C-062-5	0.062	0.438	0.187	239	48	STHT-C-375-2	0.375	0.5	0.062	17	3
STHT-C-062-6*	0.062	0.563	0.25	316	63	STHT-C-375-3	0.375	0.563	0.093	31	6
STHT-C-078-1	0.078	0.141	0.032	43	9	STHT-C-375-4	0.375	0.625	0.125	42	8
STHT-C-078-2	0.078	0.203	0.062	73	15	STHT-C-375-5	0.375	0.75	0.187	56	11
STHT-C-078-3	0.078	0.266	0.093	104	21	STHT-C-375-6	0.375	0.875	0.25	80	16
STHT-C-078-4*	0.078	0.328	0.125	135	27	STHT-C-500-1*	0.5	0.563	0.032	10	2
STHT-C-078-5	0.078	0.453	0.187	197	39	STHT-C-500-2	0.5	0.625	0.062	18	4
STHT-C-078-6	0.078	0.578	0.25	259	52	STHT-C-500-3	0.5	0.688	0.093	22	4
STHT-C-093-1	0.093	0.156	0.032	39	8	STHT-C-500-4	0.5	0.75	0.125	33	7
STHT-C-093-2	0.093	0.219	0.062	66	13	STHT-C-500-5	0.5	0.875	0.187	47	9
STHT-C-093-3	0.093	0.281	0.093	90	18	STHT-C-500-6*	0.5	1	0.25	66	13
STHT-C-093-4	0.093	0.344	0.125	104	21	STHT-C-625-1*	0.625	0.688	0.032	6	1
STHT-C-093-5*	0.093	0.469	0.187	170	34	STHT-C-625-2	0.625	0.75	0.062	13	3
STHT-C-093-6*	0.093	0.594	0.25	224	45	STHT-C-625-3*	0.625	0.813	0.093	20	4
STHT-C-125-1	0.125	0.188	0.032	32	6	STHT-C-625-4	0.625	0.875	0.125	27	5
STHT-C-125-2	0.125	0.25	0.062	52	10	STHT-C-625-5	0.625	1	0.187	42	8
STHT-C-125-3	0.125	0.313	0.093	70	14	STHT-C-625-6*	0.625	1.25	0.25	56	11
STHT-C-125-4	0.125	0.375	0.125	93	19	STHT-C-750-1*	0.75	0.813	0.032	3	1
STHT-C-125-5	0.125	0.5	0.187	114	23	STHT-C-750-2*	0.75	0.875	0.068	12	2
STHT-C-125-6	0.125	0.625	0.25	176	35	STHT-C-750-3*	0.75	0.938	0.093	16	3
STHT-C-156-1	0.156	0.219	0.032	28	6	STHT-C-750-4	0.75	1	0.125	23	5
STHT-C-156-2	0.156	0.281	0.062	44	9	STHT-C-750-5	0.75	1.125	0.187	31	6
STHT-C-156-3	0.156	0.344	0.093	55	11	STHT-C-750-6	0.75	1.25	0.25	48	10
STHT-C-156-4	0.156	0.406	0.125	77	15	STHT-C-875-1*	0.875	0.938	0.032	3	1
STHT-C-156-5*	0.156	0.531	0.187	114	23	STHT-C-875-2	0.875	1	0.062	5	1
STHT-C-156-6	0.156	0.656	0.25	148	30	STHT-C-875-3*	0.875	1.0625	0.093	11	2
STHT-C-187-1	0.187	0.25	0.032	25	5	STHT-C-875-4	0.875	1.125	0.125	18	4
STHT-C-187-2	0.187	0.313	0.062	39	8	STHT-C-875-5	0.875	1.25	0.187	30	6
STHT-C-187-3	0.187	0.375	0.093	54	11	STHT-C-875-6	0.875	1.375	0.25	42	8
STHT-C-187-4	0.187	0.438	0.125	65	13	STHT-C-1000-1*	1	1.0625	0.032	3	1
STHT-C-187-5	0.187	0.563	0.187	90	18	STHT-C-1000-2*	1	1.125	0.062	4	1
STHT-C-187-6	0.187	0.688	0.25	130	26	STHT-C-1000-3*	1	1.187	0.093	8	2
STHT-C-250-1	0.25	0.313	0.032	11	2	STHT-C-1000-4	1	1.25	0.125	18	4
STHT-C-250-2	0.25	0.375	0.062	28	6	STHT-C-1000-5	1	1.375	0.187	25	5
STHT-C-250-3	0.25	0.438	0.093	41	8	STHT-C-1000-6	1	1.5	0.25	35	7

Burst pressures are calculated at a 5:1 ratio relative to working pressure using ASTM D1599.

* Please consult factory for availability

Typical Physical Properties

Property	ASTM Method	Value or Rating (metric)
Durometer Hardness, Shore A, 15 Sec	D2240	50
Tensile Strength, psi (MPa)	D412	1250 (8.62 MPa)
Ultimate Elongation, 100%	D412	714
Tear Resistance, ppi (kN/m)	D624	250 (43.8 Kn/M)
Specific Gravity	D792	1.17
Tensile Modulus, psi (MPa)	D412	309 (2.13 MPa)

Unless otherwise noted, all tests were conducted at room temperature (73°F). Values shown were determined on 0.075" thick extruded strip or 0.075" thick molded ASTM plaques or molded ASTM durometer buttons.

Sani-Tech® STHT®-C Options

- Custom laylines
- Bulk spool packaging
- Custom sizes available
- Additional durometers available

Sterilization Methods

- Autoclavable
- Radiation – up to 5.0 Mrad (50 Kilogray)
- Gas – Ethylene Oxide

Sizing Formula

WALL 1	1/32	WALL 4	1/8
WALL 2	1/16	WALL 5	3/16
WALL 3	3/32	WALL 6	1/4

SANI-TECH® TUBING IS NOT INTENDED FOR USE AS AN IMPLANT MATERIAL

Sani-Tech® and STHT® are registered trademarks.

Saint-Gobain Performance Plastics
700 Warner Blvd.
Taunton, MA 02780
Tel: (508) 823-7701
Tel: (800) 722-7106
Fax: (508) 823-1438

Saint-Gobain Performance Plastics
Grindwell Norton Ltd,
Devanahalli Road,
Off Old Madras Road,
Bangalore, 560049, India
Tel: +91 80 28472900
Fax: +91 80 280472616



BIOPHARMACEUTICAL PRODUCTS

Come through clean.™



Saint-Gobain Performance Plastics Corporation assumes no obligations or liability for any advice furnished by it, or for results obtained with respect to those products. All such advice is given and accepted at the buyer's risk.

FLS-5065A-500-0413-SGCS

www.biopharm.saint-gobain.com

©2013 Saint-Gobain Performance Plastics Corporation